

Разделочные холодильные/морозильные столы с ящиками FFC4/2

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: fdf@nt-rt.ru || сайт: <https://foster.nt-rt.ru/>

FFC4/2: 96 Ltr Counter Vari Temp Drawer



Variable temperature two drawer reduced width counter

About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens. 35-105



Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate – change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works in hot kitchens, operating in ambient temperatures up to ISO Climate Class 5
- This is a dual refrigeration system and requires two power supplies. Data about each system can be found in the spec table “Temperature” and “Temperature 2”

Specification

Technical

Refrigerant	R290
Temperature	Freezer -18/-21°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	1.5
Power (W)	250
Refrigerant mass (g)	65
Temperature 2	Freezer -18/-21°C
Fuse rating (A) 2	10
Current (A) 2	1.5
Power (w) 2	250
Refrigerant mass (g) 2	65
Thermal heat rejection (W)	400

Dimensions

Height (mm)	900
Width (mm)	775
Depth (mm)	720
Gross volume (ltr)	48
Net volume (ltr)	48
Leg type	Roller wheels
Gross weight (kg)	138
Net weight (kg)	130.5
Gross volume (ltr) 2	48

Build

Finish ext/int	304 S/S & 304 S/S
Section configuration	
System	Integral

Energy

Climate Class	5
Energy grade	C
EEI	38.69
AEC (kWh)	1029
GWP	3
Energy grade 2	C
EEI 2	38.69
AEC (kWh) 2	1029
Energy consumption (kWh/24hr)	2.82
Energy consumption (kWh/24hr) 2	2.82

Footnotes

- Adequate airflow must be kept around the counter: 50mm
- Ecodesign data relevant per compartment
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm



FFC4/2: 96 Ltr Counter Vari Temp Drawer

35-106

Variable temperature two drawer reduced width counter with splashback

About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens.

Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate – change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 100mm 304 grade stainless steel splashback prevents spillage behind the counter
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works in hot kitchens, operating in ambient temperatures up to ISO Climate Class 5
- This is a dual refrigeration system and requires two power supplies. Data about each system can be found in the spec table “Temperature” and “Temperature 2”

Specification

Technical

Refrigerant	R290
Temperature	Freezer -18/-21°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	1.5
Power (W)	250
Refrigerant mass (g)	65
Temperature 2	Freezer -18/-21°C
Fuse rating (A) 2	10
Current (A) 2	1.5
Power (w) 2	250
Refrigerant mass (g) 2	65
Thermal heat rejection (W)	400

Dimensions

Height (mm)	950
Width (mm)	775
Depth (mm)	720
Gross volume (ltr)	48
Net volume (ltr)	48
Leg type	Braked castors
Gross weight (kg)	138
Net weight (kg)	130.5
Gross volume (ltr) 2	48

Build

Finish ext/int	304 S/S & 304 S/S
Section configuration	1/2
System	Integral
Worktop features	Splashback

Energy

Climate Class	5
Energy grade	C
EEl	38.69
AEC (kWh)	1029
GWP	3
Energy grade 2	C
EEl 2	38.69
AEC (kWh) 2	1029
Energy consumption (kWh/24hr)	2.82
Energy consumption (kWh/24hr) 2	2.82

Footnotes

- FFC4-2 requires two mains leads
- Ecodesign data relevant per compartment
- Adequate airflow must be kept around the counter: 50mm
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm



FFC4/2: 96 Ltr Counter Vari Temp Drawer

35-205

Variable temperature two drawer reduced width counter

About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens.

Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate – change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works in hot kitchens, operating in ambient temperatures up to ISO Climate Class 5
- This is a dual refrigeration system and requires two power supplies. Data about each system can be found in the spec table “Temperature” and “Temperature 2”

Specification

Technical		Dimensions	
Refrigerant	R290	Height (mm)	900
Temperature	Freezer -18/-21°C	Width (mm)	775
Electrical supply	230/50/1	Depth (mm)	720
Fuse rating (A)	10	Gross volume (ltr)	48
Power (W)	215	Net volume (ltr)	48
Refrigerant mass (g)	66	Leg type	Braked castors
Fuse rating (A) 2	10	Gross weight (kg)	138
		Net weight (kg)	130.5

Build		Energy	
Finish ext/int	304 S/S & 304 S/S	Climate Class	5
Section configuration		Energy grade	B
System	Integral	EEl	26.71
		AEC (kWh)	710.62
		GWP	3
		Energy consumption (kWh/24hr)	1.95

Footnotes

- Adequate airflow must be kept around the counter: 50mm
- Ecodesign data relevant per compartment
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm



FFC4/2: 96 Ltr Counter Vari Temp Drawer

35-206

Variable temperature two drawer reduced width counter with splashback

About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens.

Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate – change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 100mm 304 grade stainless steel splashback prevents spillage behind the counter
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works in hot kitchens, operating in ambient temperatures up to ISO Climate Class 5
- This is a dual refrigeration system and requires two power supplies. Data about each system can be found in the spec table “Temperature” and “Temperature 2”

Specification

Technical		Dimensions	
Refrigerant	R290	Height (mm)	950
Temperature	Freezer -18/-21°C	Width (mm)	775
Electrical supply	230/50/1	Depth (mm)	720
Fuse rating (A)	10	Gross volume (ltr)	48
Power (W)	215	Net volume (ltr)	48
Refrigerant mass (g)	66	Leg type	Braked castors
		Gross weight (kg)	138
		Net weight (kg)	130.5

Build		Energy	
Finish ext/int	304 S/S & 304 S/S	Climate Class	5
Section configuration	1/2	Energy grade	B
System	Integral	EEI	26.71
Worktop features	Splashback	AEC (kWh)	710.62
		GWP	3
		Energy consumption (kWh/24hr)	1.95

Footnotes

- FFC4-2 requires two mains leads
- EcoDesign data relevant per compartment
- Adequate airflow must be kept around the counter: 50mm
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: fdf@nt-rt.ru || сайт: <https://foster.nt-rt.ru/>