

Разделочные холодильные/морозильные столы с ящиками FFC2/1

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: fdf@nt-rt.ru || сайт: <https://foster.nt-rt.ru/>



FFC2/1: 48 Ltr Counter Vari Temp Drawer

35-107

Variable temperature one drawer reduced width counter

About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens.



Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate - change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works in hot kitchens, operating in ambient temperatures up to ISO Climate Class 5

Specification

Technical		Dimensions	
Refrigerant	R290	Height (mm)	600
Temperature	Freezer -18/-21°C	Width (mm)	775
Electrical supply	230/50/1	Depth (mm)	720
Fuse rating (A)	10	Gross volume (ltr)	48
Current (A)	1.5	Net volume (ltr)	48
Power (W)	250	Leg type	Braked castors
Refrigerant mass (g)	65	Gross weight (kg)	88
Thermal heat rejection (W)	200	Net weight (kg)	80.5

Build		Energy	
Finish ext/int	304 S/S & 304 S/S	Climate Class	5
Section configuration		Energy grade	C
System	Integral	EEl	38.69
		AEC (kWh)	1029
		GWP	3
		Energy consumption (kWh/24hr)	2.82

Footnotes

- Adequate airflow must be kept around the counter: 50mm
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

Product specification



FFC2/1: 48 Ltr Counter Vari Temp Drawer

35-108

Variable temperature one drawer reduced width counter with splashback

About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens.

Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate – change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works in hot kitchens, operating in ambient temperatures up to ISO Climate Class 5

Specification

Technical		Dimensions	
Refrigerant	R290	Height (mm)	650
Temperature	Freezer -18/-21°C	Width (mm)	775
Electrical supply	230/50/1	Depth (mm)	720
Fuse rating (A)	10	Gross volume (ltr)	48
Current (A)	1.5	Net volume (ltr)	48
Power (W)	250	Leg type	Braked castors
Refrigerant mass (g)	65	Gross weight (kg)	88
Thermal heat rejection (W)	200	Net weight (kg)	80.5

Build		Energy	
Finish ext/int	304 S/S & 304 S/S	Climate Class	5
Section configuration		Energy grade	C
		EEl	38.69
System	Integral	AEC (kWh)	1029
Worktop features	Splashback	GWP	3
		Energy consumption (kWh/24hr)	2.82

Footnotes

- Adequate airflow must be kept around the counter: 50mm
- Ecodesign data relevant per compartment
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

Product specification



FFC2/1: 48 Ltr Counter Vari Temp Drawer

35-207

Variable temperature one drawer reduced width counter

About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens.

Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate – change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works in hot kitchens, operating in ambient temperatures up to ISO Climate Class 5

Specification

Technical

Refrigerant	R290
Temperature	Freezer -18/-21°C
Electrical supply	230/50/1
Fuse rating (A)	10
Power (W)	225
Refrigerant mass (g)	66

Dimensions

Height (mm)	600
Width (mm)	755
Depth (mm)	720
Gross volume (ltr)	48
Net volume (ltr)	48
Leg type	Braked castors
Gross weight (kg)	88
Net weight (kg)	80.5

Build

Finish ext/int	304 S/S & 304 S/S
Section configuration	
System	Integral

Energy

Climate Class	5
Energy grade	C
EEl	39.27
AEC (kWh)	1044.75
GWP	3
Energy consumption (kWh/24hr)	2.86

Footnotes

- Adequate airflow must be kept around the counter: 50mm
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

Product specification



FFC2/1: 48 Ltr Counter Vari Temp Drawer

35-208

Variable temperature one drawer reduced width counter with splashback

About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens.

Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate – change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works in hot kitchens, operating in ambient temperatures up to ISO Climate Class 5

Specification

Technical

Refrigerant	R290
Temperature	Freezer -18/-21°C
Electrical supply	230/50/1
Fuse rating (A)	10
Power (W)	225
Refrigerant mass (g)	66

Dimensions

Height (mm)	650
Width (mm)	775
Depth (mm)	720
Gross volume (ltr)	48
Net volume (ltr)	48
Leg type	Braked castors
Gross weight (kg)	88
Net weight (kg)	80.5

Build

Finish ext/int	304 S/S & 304 S/S
Section configuration	
System	Integral
Worktop features	Splashback

Energy

Climate Class	5
Energy grade	C
EEl	39.27
AEC (kWh)	1044.75
GWP	3
Energy consumption (kWh/24hr)	2.86

Footnotes

- Adequate airflow must be kept around the counter: 50mm
- Ecodesign data relevant per compartment
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: fdf@nt-rt.ru || сайт: <https://foster.nt-rt.ru/>