

# Холодильные/морозильные шкафы EcoPro G3 EP700HL, EP700SH, EP700SL

## Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: [fdf@nt-rt.ru](mailto:fdf@nt-rt.ru) || сайт: <https://foster.nt-rt.ru/>



## EP700HL: 600 Ltr Cabinet Dual Temperature

41-487

Dual temperature cabinet

### About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

## Why choose this product

- This model offers refrigerator and freezer temperatures in the same cabinet – perfect for when space is at a premium
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Market leading usable capacity, now supplied with 4 shelves as standard making your money go further – holds more than a conventional fridge
- Operates in ambient temperatures of up to 43°C
- This is a dual refrigeration system and requires two power supplies. Data about each system can be found in the spec table "Temperature" and "Temperature 2"

## Specification

### Technical

<b>Refrigerant</b>	R290
<b>Temperature</b>	Refrigerator +1/+4°C
<b>Electrical supply</b>	230/50/1
<b>Fuse rating (A)</b>	10
<b>Current (A)</b>	1.6
<b>Power (W)</b>	240
<b>Refrigerant mass (g)</b>	65
<b>Temperature 2</b>	Freezer -18/-21°C
<b>Fuse rating (A) 2</b>	10
<b>Current (A) 2</b>	2.8
<b>Power (w) 2</b>	475
<b>Refrigerant mass (g) 2</b>	65
<b>Thermal heat rejection (W)</b>	480

### Dimensions

<b>Height (mm)</b>	2080
<b>Width (mm)</b>	700
<b>Depth (mm)</b>	825
<b>Gross volume (litr)</b>	270
<b>Net volume (litr)</b>	177.4
<b>Leg type</b>	Braked castors
<b>Gross weight (kg)</b>	155
<b>Net weight (kg)</b>	149
<b>Gross volume (litr) 2</b>	270

### Build

<b>Cabinet type</b>	Dual temperature
<b>Finish ext/int</b>	S/S & Alu
<b>Number of sections</b>	1
<b>Section configuration</b>	Right hinge
<b>System</b>	Integral

### Energy

<b>Climate Class</b>	5
<b>Energy grade</b>	C
<b>EEL</b>	42.47
<b>AEC (kWh)</b>	382.48
<b>GWP</b>	3
<b>Energy grade 2</b>	D
<b>EEL 2</b>	53.73
<b>AEC (kWh) 2</b>	1261
<b>Energy consumption (kWh/24hr)</b>	1.0479
<b>Energy consumption (kWh/24hr) 2</b>	3.45

### Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 100mm
- Depth with door open is 1500mm
- This is a dual refrigeration system – data about each system can be found in the spec table above for example “Temperature” and “Temperature 2”



## EP700HL: 600 Ltr Cabinet Dual Temperature

41-489

### About the product

### Why choose this product

The two-door model has two separate compartments, each with its own cooling system

The new, improved +StayClear condenser extends the service life and reduces energy consumption. With the +StayClear, your refrigerator always remains an energy-saving refrigerator.

Foster Shield's advanced temperature control and hygienic design provide protection against food safety hazards. The airflow system optimised by CFD design technology ensures efficient operation even when shelves are fully loaded

With PureControl, the display of the G3 controller features pure LEDs with InGaN technology, achieving higher resolution, lasting longer – and consuming less power. Equipped with an RS485 interface, connectivity is guaranteed for the future

All doors and covers of the G3 are made of high-quality 304 chrome-nickel steel – the "gold standard" for stainless steel – meaning that the most frequently touched areas of the device are covered

With market-leading capacity and 4 shelves as standard, you get more for your money – more space than in a conventional refrigerator

Operates at ambient temperatures up to 43 °C

# Specification

## Technical

Refrigerant	R290
Temperature	Refrigerator +1/+4°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	1.6
Power (W)	240
Refrigerant mass (g)	65
Thermal heat rejection (W)	480

## Dimensions

Height (mm)	2080
Width (mm)	700
Depth (mm)	825
Gross volume (ltr)	270
Net volume (ltr)	177.4
Leg type	Castors
Gross weight (kg)	155
Net weight (kg)	149

## Build

Cabinet type	Dual temperature , Half door
Door material	304 Stainless steel
Finish ext/int	S/S & S/S
Section configuration	Right hinge
System	Integral

## Energy

Climate Class	5
Energy grade	C
EEl	42.47
AEC (kWh)	382.48
GWP	3
Energy consumption (kWh/24hr)	1.0479



## EP700HL: 600 Ltr Cabinet Dual Temperature

41-697

Dual temperature cabinet

### About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

## Why choose this product

- This model offers refrigerator and freezer temperatures in the same cabinet – perfect for when space is at a premium
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Market leading usable capacity, now supplied with 4 shelves as standard making your money go further – holds more than a conventional fridge
- Operates in ambient temperatures of up to 43°C
- This is a dual refrigeration system and requires two power supplies. Data about each system can be found in the spec table "Temperature" and "Temperature 2"

## Specification

### Technical

<b>Refrigerant</b>	R290
<b>Temperature</b>	Refrigerator +1/+4°C
<b>Electrical supply</b>	230/50/1
<b>Fuse rating (A)</b>	10
<b>Current (A)</b>	1.6
<b>Power (W)</b>	240
<b>Refrigerant mass (g)</b>	65
<b>Temperature 2</b>	Freezer -18/-21°C
<b>Fuse rating (A) 2</b>	10
<b>Current (A) 2</b>	2.80
<b>Power (w) 2</b>	475
<b>Refrigerant mass (g) 2</b>	65

### Dimensions

<b>Height (mm)</b>	2080
<b>Width (mm)</b>	700
<b>Depth (mm)</b>	825
<b>Gross volume (ltr)</b>	270
<b>Net volume (ltr)</b>	177.4
<b>Leg type</b>	Braked castors
<b>GN size</b>	2/1
<b>Gross weight (kg)</b>	155
<b>Net weight (kg)</b>	149
<b>Gross volume (ltr) 2</b>	270

### Build

<b>Cabinet type</b>	Dual temperature
<b>Door material</b>	304 Stainless steel
<b>Finish ext/int</b>	304 S/S & 304 S/S
<b>Section configuration</b>	Right hinge
<b>System</b>	Integral

### Energy

<b>Climate Class</b>	5
<b>Energy grade</b>	C
<b>EEI</b>	42.47
<b>AEC (kWh)</b>	382.48
<b>GWP</b>	3
<b>Energy grade 2</b>	D
<b>EEI 2</b>	53.73
<b>AEC (kWh) 2</b>	1261
<b>Energy consumption (kWh/24hr)</b>	1.0479
<b>Energy consumption (kWh/24hr) 2</b>	3.45

### Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 100mm
- Depth with door open is 1500mm



## EP700SH: 550 Ltr Cabinet Refrigerator

41-761

Single door low height refrigerator cabinet

### About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

## Why choose this product

- Suitable for low ceiling height applications
- Lower energy consumption & 33% energy saving vs previous model
- All the benefits of the standard G3, but this product can fit through a standard (1960 x 760) doorway without tilting
- With this model's smaller footprint, it is a great option where available kitchen space is an issue
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Greater usable internal storage capacity – an increase of 28 litres over the previous model
- Fully GN 2/1 shelving compatible
- Operates in ambient temperatures of up to 43°C

## Specification



Technical

Refrigerant	R290
Temperature	Refrigerator +1/ +4°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	0.6
Power (W)	140
Refrigerant mass (g)	80
Thermal heat rejection (W)	140

Dimensions

Height (mm)	1955
Width (mm)	700
Depth (mm)	855
Gross volume (ltr)	550
Net volume (ltr)	439.6
Leg type	Braked castors
GN size	2/1
Gross weight (kg)	124
Net weight (kg)	99.5

Build

Cabinet type	Short
Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Right hinge
System	Integral

Energy

Climate Class	5
Energy grade	A
EEl	24.01
AEC (kWh)	319.6
GWP	3
Energy consumption (kWh/24hr)	0.88

Footnotes

- Requires 100mm free space above product



## EP700SH: 550 Ltr Cabinet Refrigerator

41-762

Single door low height refrigerator cabinet

### About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

## Why choose this product

- Suitable for low ceiling height applications
- Lower energy consumption & 33% energy saving vs previous model
- All the benefits of the standard G3, but this product can fit through a standard (1960 x 760) doorway without tilting
- With this model's smaller footprint, it is a great option where available kitchen space is an issue
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Greater usable internal storage capacity – an increase of 28 litres over the previous model
- Fully GN 2/1 shelving compatible
- Operates in ambient temperatures of up to 43°C

## Specification

Technical

Refrigerant	R290
Temperature	Refrigerator +1/ +4°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	0.6
Power (W)	140
Refrigerant mass (g)	80
Thermal heat rejection (W)	140

Dimensions

Height (mm)	1955
Width (mm)	700
Depth (mm)	855
Gross volume (ltr)	550
Net volume (ltr)	439.6
Leg type	Braked castors
GN size	2/1
Gross weight (kg)	124
Net weight (kg)	99.5

Build

Cabinet type	Short
Finish ext/int	304 S/S & 304 S/S
Number of sections	1
Section configuration	Right hinge
System	Integral

Energy

Climate Class	5
Energy grade	A
EEl	24.01
AEC (kWh)	319.6
GWP	3
Energy consumption (kWh/24hr)	0.88

Footnotes

- Requires 100mm free space above product



## EP700SL: 550 Ltr Cabinet Freezer

41-766

Single door low height freezer cabinet

### About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

## Why choose this product

- Suitable for low ceiling height applications
- Lower energy consumption & 33% energy saving vs previous model
- All the benefits of the standard G3, but this product can fit through a standard (1960 x 760) doorway without tilting
- With this model's smaller footprint, it is a great option where available kitchen space is an issue
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Greater usable internal storage capacity – an increase of 28 litres over the previous model
- Fully GN 2/1 shelving compatible
- Operates efficiently in ambient temperatures of up to 43°C

## Specification

Technical		Dimensions	
Refrigerant	R290	Height (mm)	1955
Temperature	Freezer -18/-21°C	Width (mm)	700
Electrical supply	230/50/1	Depth (mm)	855
Fuse rating (A)	10	Gross volume (ltr)	550
Current (A)	1.2	Net volume (ltr)	439.6
Power (W)	270	Leg type	Braked castors
Refrigerant mass (g)	80	GN size	2/1
Thermal heat rejection (W)	330	Gross weight (kg)	124
		Net weight (kg)	99.5

Build		Energy	
Cabinet type	Short	Climate Class	5
Finish ext/int	304 S/S & 304 S/S	Energy grade	B
		EEI	31.9
Number of sections	1	AEC (kWh)	1161
Section configuration	Right hinge	GWP	3
System	Integral	Energy consumption (kWh/24hr)	3.18

Footnotes

- Requires 100mm free space above product



## EP700SH: 550 Ltr Cabinet Refrigerator

41-763

Single door low height refrigerator cabinet

### About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

## Why choose this product

- Suitable for low ceiling height applications
- Lower energy consumption & 33% energy saving vs previous model
- All the benefits of the standard G3, but this product can fit through a standard (1960 x 760) doorway without tilting
- With this model's smaller footprint, it is a great option where available kitchen space is an issue
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Greater usable internal storage capacity – an increase of 28 litres over the previous model
- Fully GN 2/1 shelving compatible
- Operates in ambient temperatures of up to 43°C

## Specification

Technical

Refrigerant	R290
Temperature	Refrigerator +1/ +4°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	0.6
Power (W)	140
Refrigerant mass (g)	80
Thermal heat rejection (W)	140

Dimensions

Height (mm)	1955
Width (mm)	700
Depth (mm)	855
Gross volume (ltr)	550
Net volume (ltr)	439.6
Leg type	Braked castors
GN size	2/1
Gross weight (kg)	124
Net weight (kg)	99.5

Build

Cabinet type	Short
Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Left hinge
System	Integral

Energy

Climate Class	5
Energy grade	A
EEL	24.01
AEC (kWh)	319.6
GWP	3
Energy consumption (kWh/24hr)	0.88

Footnotes

- Requires 100mm free space above product



## EP700SL: 550 Ltr Cabinet Freezer

41-767

Single door short freezer cabinet

### About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

## Why choose this product

- Suitable for low ceiling height applications
- Lower energy consumption & 33% energy saving vs previous model
- All the benefits of the standard G3, but this product can fit through a standard (1960 x 760) doorway without tilting
- With this model's smaller footprint, it is a great option where available kitchen space is an issue
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Greater usable internal storage capacity – an increase of 28 litres over the previous model
- Fully GN 2/1 shelving compatible
- Operates in ambient temperatures of up to 43°C

## Specification



Technical

Refrigerant	R290
Temperature	Freezer -18/-21°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	1.2
Power (W)	270
Refrigerant mass (g)	80
Thermal heat rejection (W)	330

Dimensions

Height (mm)	1955
Width (mm)	700
Depth (mm)	855
Gross volume (ltr)	550
Net volume (ltr)	439.6
Leg type	Braked castors
GN size	2/1
Gross weight (kg)	124
Net weight (kg)	99.5

Build

Cabinet type	Short
Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Left hinge
System	Integral

Energy

Climate Class	5
Energy grade	B
EEl	31.9
AEC (kWh)	1161
GWP	3
Energy consumption (kWh/24hr)	3.18

Footnotes

- Requires 100mm free space above product



## EP700SL: 550 Ltr Cabinet Freezer

41-765

Single door low height freezer cabinet

### About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

## Why choose this product

- Suitable for low ceiling height applications
- Lower energy consumption & 33% energy saving vs previous model
- All the benefits of the standard G3, but this product can fit through a standard (1960 x 760) doorway without tilting
- With this model's smaller footprint, it is a great option where available kitchen space is an issue
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Greater usable internal storage capacity – an increase of 28 litres over the previous model
- Fully GN 2/1 shelving compatible
- Operates in ambient temperatures of up to 43°C

## Specification

Technical

Refrigerant	R290
Temperature	Freezer -18/-21°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	1.2
Power (W)	270
Refrigerant mass (g)	80
Thermal heat rejection (W)	330

Dimensions

Height (mm)	1955
Width (mm)	700
Depth (mm)	855
Gross volume (ltr)	550
Net volume (ltr)	439.6
Leg type	Braked castors
GN size	2/1
Gross weight (kg)	124
Net weight (kg)	99.5

Build

Cabinet type	Short
Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Right hinge
System	Integral

Energy

Climate Class	5
Energy grade	B
EEL	31.9
AEC (kWh)	1161
GWP	3
Energy consumption (kWh/24hr)	3.18

Footnotes

- Requires 100mm free space above product

## По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

**Россия** +7(495)268-04-70

**Казахстан** +(727)345-47-04

**Беларусь** +(375)257-127-884

**Узбекистан** +998(71)205-18-59

**Киргизия** +996(312)96-26-47

эл.почта: [fdf@nt-rt.ru](mailto:fdf@nt-rt.ru) || сайт: <https://foster.nt-rt.ru/>